

# 1

## **Prepare The Area**

Measure the area to determine the exact placement of your letters or graphics. Make sure the area is clean and free of dust by wiping the surface with a clean dry cloth.

# 4

## **Remove The Pattern**

Partially peel back the pattern from one corner to determine if the chalk outline is visible enough. If the outline is not visible enough, gently reposition the pattern and tap with chalk bag.

# 2

## **Attach The Pattern**

Properly position the pattern on the surface, making sure the baseline of the pattern is level. Attach the pattern to the surface by securely taping the corners and sides to prevent movement.

# 5

## **Placing Letters or Graphics**

Remove any backing from the adhesive on each element and gently place them inside the chalk outline. Making sure each element is properly aligned, apply pressure to ensure a secure bond.



# 3

## **Transfer The Pattern**

Gently begin to tap the chalk bag over all the holes in the pattern. The harder the tapping the more visible the outline will be.



**chesapeake**  
**SIGN**  
**company**<sup>INC</sup>

**10540 York Road**  
**Suite E**

**410-66-SIGNS (74467)**

**Fax: 410-667-4469**

**[www.chesapeakeesign.com](http://www.chesapeakeesign.com)**

**[info@chesapeakeesign.com](mailto:info@chesapeakeesign.com)**